

# SILEX+ SMALL

THE MODEL WITHOUT COMPROMISE, SMALLER FIT

Specifically developed for smaller and narrower faces, SILEX+ SMALL adopts all the feature of the Silex+ model, just in a smaller fit. Suitable for all industries, this model combines superior protection with style. Enhanced safety with its co-injected FLEX 160° temples and exclusive PLATINUM® coating on both sides of the lens.

✦ PLATINUM®



PSSSILP0402 : Clear Lens



PSSSILP4262 : Smoke Lens



PSSSILPC092 : CSP Lens



26g



PSSSILP0402 + PSPUNISS01















PSPUNISS01 (optional)  
Strap

- ✦ ULTRA WRAP-AROUND FRAME
- ✦ ✦ PLATINUM® ( ✦ P ) SCRATCH & FOG RESISTANT COATING
- ✦ CO-INJECTED PC/TPR TEMPLES FOR GREATER COMFORT
- ✦ PANORAMIC FIELD OF VISION
- ✦ FLEX 160° TEMPLES


**bolle**  
SAFETY

# SILEX+ SMALL

THE MODEL WITHOUT COMPROMISE, SMALLER FIT

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SILEX+ SMALL	 Clear	PSSSILP0402 	IO & 	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/Platinum 
	 Smoke	PSSSILP4262 	I3 & 	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/Platinum 
	 CSP	PSSSILPC092 	I1 & 	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/Platinum 
	Strap only (optional)	PSPUNISS01	-	-	-

## LENS MARKING

. Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m<sup>2</sup>) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.

I. The letter 'I' signifies 'Medium Impact' approval.

O. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

## Ocular lens category:

O. Range of luminous transmittance 80–100% (Clear)

1. Range of luminous transmittance 43–88% (CSP).

3. Range of luminous transmittance 8–18% (Smoke)

## Others symbols:

 Manufacturer name

## FRAME MARKING

AS/NZS 1337.1:2010 : Tested and approved to AS/NZS 1337.1:2010 for medium impact protection. Resists a 6mm ball at 45 m/s.

## LENSES

- 2mm polycarbonate
- Platinum coating on both sides of Clear, Smoke and CSP lens
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke and CSP

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

## TECHNOLOGIES

### CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

### PLATINUM®

The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

### FLEX 160°

Soft and ultra pliable, 160° FLEX frames can be used to adjust the space between the temples for better wearer comfort.

## PACKAGING AND EAN13 CODE

	PSSSILP0402	PSSSILP4262	PSSSILPC092
Individual plastic bag	3660740011673	3660740011680	3660740011697
10 safety spectacles per inner box	3660740111670	3660740111687	3660740111694
240 safety spectacles per outer pack	3660740211677	3660740211684	3660740211691

Individual polybag: 155x60x55mm // 30g  
Inner bog: 23.8x18x9cm // 500g  
Outer pack: 60x50x37cm // 15.1kg

## CHARACTERISTICS

LENSES	PC – 2,2mm – Curve 9
FRAME	–
TEMPLES	PC + TPR
STRAP	Nylon/15mm/Adjustable
SPARE LENSES	No



09/07/2021

Bollé Safety AU Pty Limited  
32–40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: sales@bollesafety.com.au

Hong Kong Bollé Safety  
818, 8/F, Ocean Centre, Harbour City,  
5 Canton Road, Tsim Sha Tsui,  
Kowloon, Hong Kong  
T.: +852 2732 5038

bollesafety.com.au

**bolle**  
SAFETY